

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 September 2003 (04.09.2003)


PCT

(10) International Publication Number
WO 03/073481 A2

- (51) International Patent Classification⁷: **H01L 21/00**
- (21) International Application Number: **PCT/US03/07264**
- (22) International Filing Date: 24 February 2003 (24.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/359,222 22 February 2002 (22.02.2002) US
- (71) Applicant (for all designated States except US): **AGERE SYSTEMS, INC.** [US/US]; 555 Union Boulevard, Allentown, PA 18109 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HOUGE, Erik, C.** [US/US]; 6237 Bent Pine Drive, Orlando, FL 32822 (US). **KEMPSHALL, Brian** [US/US]; ** (US). **SCHWARTZ, Steve** [US/US]; ** (US). **STEVIE, F. A.** [US/US]; 102 Colinsburgh Court, Cary, NC 27511 (US).
- (74) Agents: **BEUSSE, James, H. et al.**; Beusse Brownlee Bowdoin & Wolter, P.A., 390 N. Orange Avenue, Suite 2500, Orlando, FL 32801 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: CRYSTALLOGRAPHIC METROLOGY AND PROCESS CONTROL



(57) Abstract: A system (70) for crystallography including a sample holder (74), an electron source (76) for generating an electron beam, and a scanning actuator (80) for controlling the relative movement between the electron beam and the crystalline sample, the scanning actuator being controllable for directing the electron beam at a series of spaced apart points within the sample area. The system also includes an image processor (84) for generating crystallographic data based upon electron diffraction from the crystalline sample and for determining whether sufficient data have been acquired to characterize the sample area. The system further includes a controller (86) for controlling the scanning actuator to space the points apart such that acquired data is representative of a different grains within the crystalline sample. IN other embodiments, the invention includes one or more ion beams (178, 188) for crystallography and a combination ion beam/electron beam (218, 228).